

# Toyana NUP1021 cylindrical roller bearings

Shop Toyana NUP1021 cylindrical roller bearings huge online discount inventory. 75x160x55 Size (mm) and Import machinery parts your car needs with Free Shipping and Free Extended 160 Outer Diameter (mm) Warranty.

Size (mm)	75x160x55
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Width (mm)	55
d	75 mm
D	160 mm
B	55 mm
C	55 mm
r min.	2,1 mm
da min.	87 mm
da max	97 mm
Da min	137 mm
Da max.	148 mm
ra max.	2 mm
Weight	5,26 Kg
Basic dynamic load rating (C)	390 kN
Basic static load rating (C0)	505 kN
(Grease) Lubrication Speed	2600 r/min
(Oil) Lubrication Speed	3200 r/min
Calculation factor (e)	0,33
Calculation factor (Y0)	2

Calculation factor (Y2)	3
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	5.3
EAN	0029176411816
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Inch – Metric	Metric
Long Description	75MM Straight Bore; 160MM Outside Diameter; 55MM Width; C0-Medium Clearance; Shaft Mount; Double Row
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	22315EAE4
Weight / LBS	5.3
Outside Diameter	6.299 Inch   160 Millimeter
Adapter Part Number	Not Applicable Inch   Not Applicable Millimeter

Bore	2.953 Inch   75 Millimeter
Width	2.165 Inch   55 Millimeter
bore diameter:	75 mm
maximum rpm:	3600 RPM
outside diameter:	160 mm
operating temperature range:	Maximum of +200 °C
overall width:	55 mm
cage material:	Steel
bore type:	Straight
bearing material:	Steel
outer ring type:	Not Split
cage type:	Roller Guided
internal clearance:	C0
precision rating:	RBEC 1 (ISO Class Normal)
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	55 mm
dynamic load capacity:	485000 N
fillet radius:	2.1 mm
static load capacity:	505000 N
series:	223
Y3	2
hidYobi	22315EAE4
LangID	1
Y1	2
D_	160
Y2	3
Macha rpm	4300

B_	55
da min	87
hidTable	ecat_NSSPHR
Oil rpm	3600
Y0	2
mass	5.26
GRS rpm	2800
ra	2
TSR rpm	3400
C0	505
DE_	142.493
X0	1
Prod_Type3	SRB_CTB_CB
X1	1
X2	0.67
SIR	22.42
e	0.33
DA_	21.25
bomp	22315EAE4
Z_	16
ALP2	35
ALP1	12
ALP3	0
D_a max	148
D_a min	137
yobi	22315EAE4
HPS	HPS
ALPHA_	0.22
SDM_	121.754

r	2.1
KBRG	2328
SBRG	23
DI_	101.014