

Toyana NUP2324 E cylindrical roller bearings

Request A Quote 52x20x15 Size (mm) 52 Bore Diameter (mm) For Your Special Toyana NUP2324 E cylindrical roller bearings Needs Today! Free Quotes. ISO 9001 certified.

Size (mm)	52x20x15
Bore Diameter (mm)	52
Outer Diameter (mm)	20
Width (mm)	15
d	20 mm
D	52 mm
B	15 mm
d1	30 mm
D2	45.4 mm
r1,2 – min.	1.1 mm
da – min.	26.5 mm
Da – max.	46 mm
ra – max.	1 mm
Basic dynamic load rating – C	13.8 kN
Basic static load rating – C0	7.8 kN
Fatigue load limit – Pu	0.335 kN
Reference speed	34000 r/min
Limiting speed	20000 r/min
Calculation factor – kr	0.035
Calculation factor – f0	12.3
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.3086
Bore	0.787 Inch 20 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Inner Race Width	0 Inch 0 Millimeter
d1 ≈	30 mm
D2 ≈	45.4 mm
r1,2 min.	1.1 mm
da min.	26.5 mm

Da max.	46 mm
ra max.	1 mm
Basic dynamic load rating C	13.8 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Calculation factor kr	0.035
Calculation factor f0	12.3
Mass bearing	0.14 kg