

Toyana NUP2336 E cylindrical roller bearings

Find the discount Toyana NUP2336 E cylindrical roller bearings online you need . We offer ... If you check out our large selection of Toyana NUP2336 E cylindrical roller bearings 170 Bore Diameter (mm) once 170x110x45 Size (mm) .

Size (mm)	170x110x45
Bore Diameter (mm)	170
Outer Diameter (mm)	110
Width (mm)	45
d	110 mm
D	170 mm
B	45 mm
d2	125 mm
D1	151 mm
b	6 mm
K	3 mm
r1,2 – min.	2 mm
da – min.	119 mm
Da – max.	161 mm
ra – max.	2 mm
Basic dynamic load rating – C	326 kN
Basic static load rating – C0	440 kN
Fatigue load limit – Pu	46.5 kN
Reference speed	3400 r/min
Limiting speed	4300 r/min
Calculation factor – e	0.23

Calculation factor – Y1	2.9
Calculation factor – Y2	4.4
Calculation factor – Y0	2.8
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.769
EAN	7316577033024
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch – Metric	Metric
Long Description	110MM Straight Bore; 170MM Outside Diameter; 45MM Width; C0-Medium Clearance; Shaft Mount; Double Ro
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	8.302
Width	1.772 Inch 45 Millimeter

Bore	4.331 Inch 110 Millimeter
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Outside Diameter	6.693 Inch 170 Millimeter
bore diameter:	110 mm
maximum rpm:	4300 RPM
outside diameter:	170 mm
operating temperature range:	Maximum of +390 °F
overall width:	45 mm
cage material:	Steel
bore type:	Straight
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	45 mm
dynamic load capacity:	310 kN
fillet radius:	2 mm
static load capacity:	440 kN
series:	230
d2 ≈	125 mm
D1 ≈	151 mm
r1,2 min.	2 mm
da min.	119 mm
Da max.	161 mm

ra max.	2 mm
Basic dynamic load rating C	326 kN
Basic static load rating C0	440 kN
Fatigue load limit Pu	46.5 kN
Calculation factor e	0.23
Calculation factor Y1	2.9
Calculation factor Y2	4.4
Calculation factor Y0	2.8
Mass bearing	3.8 kg