

Toyana NUP2344 E cylindrical roller bearings

Enjoy High 65 Bore Diameter (mm) Margins on Competitive Pricing.Great Wholesale Products at 65x140x36 Size (mm) Low Costs.

| | |
|---------------------|-----------|
| Size (mm) | 65x140x36 |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 140 |
| Width (mm) | 36 |
| d | 65 mm |
| D | 140 mm |
| T | 36 mm |
| a | 44 mm |
| B | 33 mm |
| C | 23 mm |
| Ca min | 5 mm |
| Cb min | 13 mm |
| Da max | 128 mm |
| Da min | 111 mm |
| Db min | 132 mm |
| d1 | 102,6 mm |
| da max | 79 mm |
| db min | 77 mm |
| r1, 2 min | 3 mm |
| r3, 4 min | 2,5 mm |
| ra max | 3 mm |
| rb max | 2,5 mm |

| | |
|-----|--|
| m | 2,36 kg / Weight |
| Cr | 163000 N |
| C0r | 188000 N / Static load rating (radial) |
| e | 0,83 |
| Y | 0,73 |
| Y0 | 0,4 |
| Cur | 22300 N / Fatigue limit load, radial |
| nG | 5000 1/min / Limiting speed |
| nB | 3600 1/min / Reference speed |