

Toyana NUP2352 E cylindrical roller bearings

LET 75x45x19 Size (mm) OUR Toyana NUP2352 E cylindrical roller bearings 75 Bore Diameter (mm) EXPERTS GET YOU THE PARTS YOU NEED.

Size (mm)	75x45x19
Bore Diameter (mm)	75
Outer Diameter (mm)	45
Width (mm)	19
d	45 mm
D	75 mm
B	19 mm
d1	56 mm
D1	65.5 mm
F	52.5 mm
r1,2 – min.	1 mm
r3,4 – min.	1 mm
s	0.7 mm
da – min.	57 mm
da – max.	51 mm
db – min.	57.5 mm
Da – max.	69.8 mm
ra – max.	1 mm
Basic dynamic load rating – C	52.8 kN
Basic static load rating – C0	64 kN
Fatigue load limit – Pu	7.8 kN
Reference speed	9000 r/min

Limiting speed	11000 r/min
Calculation factor – kr	0.1
d1 ≈	56 mm
D1 ≈	65.5 mm
r1,2 min.	1 mm
r3,4 min.	0.6 mm
s max.	0.7 mm
da min.	57 mm
da max.	51 mm
db min.	57.5 mm
Da max.	69.8 mm
ra max.	1 mm
Basic dynamic load rating C	52.8 kN
Basic static load rating C0	64 kN
Fatigue load limit Pu	7.8 kN
Calculation factor kr	0.13
Limiting value e	0.3
Axial load factor Y	0.4
Mass bearing	0.3 kg