

# Toyana NUP3336 cylindrical roller bearings

What is Toyana NUP3336 cylindrical roller bearings in mechanical engineering? Manufacturing Service . Upload your 35x72x17 Size (mm) CAD file for an instant.

Size (mm)	35x72x17
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Width (mm)	17
d	35 mm
D	72 mm
B	17 mm
C	17 mm
d1	46,9 mm
d2	– mm
r1 min.	42 mm
r2 min.	42 mm
D1	62,7 mm
D2	1,1 mm
da min.	42 mm
Da max.	65 mm
ra max.	1 mm
Weight	0,3 Kg
Basic dynamic load rating (C)	27 kN
Basic static load rating (C0)	15,3 kN
Fatigue load limit (Pu)	0,655
Reference speed	20000 r/min

Limiting speed	10000 r/min
Calculation factor (f0)	14
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.297
EAN	7316575801205
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 1 Metal Shield; Ball Bearing; ABEC 1   ISO
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6207-Z
Weight / LBS	0.6724
Outside Diameter	2.835 Inch   72 Millimeter
Inner Race Width	0 Inch   0 Millimeter

Bore	1.378 Inch   35 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
d1 ≈	46.94 mm
D2 ≈	62.69 mm
r1,2 min.	1.1 mm
da max.	46.8 mm
Basic dynamic load rating C	27 kN
Basic static load rating C0	15.3 kN
Fatigue load limit Pu	0.655 kN
Calculation factor kr	0.025
Calculation factor f0	13.8
Mass bearing	0.29 kg