

Toyana RNA4905-2RS needle roller bearings

Question Toyana RNA4905-2RS needle roller bearings ? Find what 10x26x8 Size (mm) you need faster by entering your information

| | |
|-------------------------------|------------------|
| Size (mm) | 10x26x8 |
| Bore Diameter (mm) | 10 |
| Outer Diameter (mm) | 26 |
| Width (mm) | 8 |
| d | 10 mm |
| D | 26 mm |
| B | 8 mm |
| C | 8 mm |
| Angle (α) | 30 ° |
| a | 1.2 mm |
| r min. | 0.3 mm |
| r1 min. | 0.15 mm |
| 2B | 16 mm |
| da min. | 12 mm |
| Da max. | 25 mm |
| ra max. | 0.15 mm |
| Weight | 0.022 Kg |
| Basic dynamic load rating (C) | 8,15 kN |
| Basic static load rating (C0) | 4,65 kN |
| (Grease) Lubrication Speed | 19000 r/min |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |

| | |
|-------------------------|------------|
| Configuration | Duplex |
| Bore Size | 10 mm |
| Outside Diameter | 26 mm |
| Width | 8 mm |
| Fillet Radius/Chamfer | 0.3 mm |
| r1 | 0.2 mm |
| Dynamic Load Rating | 8,150 N |
| Static Load Rating | 4,650 N |
| Limiting Speed – Grease | 19,000 rpm |
| Limiting Speed – Oil | 26,000 rpm |
| da1 (min) | 12 mm |
| da2 (min) | 12 mm |
| Da1 (max) | 24 mm |
| Da2 (max) | 25 mm |
| ra (max) | 0.3 mm |
| ra1 (max) | 0.2 mm |