

# Toyana TUP1 220.80 plain bearings

What is the best place to buy Toyana TUP1 220.80 plain bearings online? Manufacturing Service 50 mm d .

d	50 mm
D	110 mm
B	40 mm
C	33 mm
T	42.25 mm
d1	78.5 mm
a	28.5 mm
rs min	2.5 mm
r1s min	2 mm
e	0.35
Y2	1.74
Y0	0.96
Mass	1.92 kg
ISO 355 reference	T2FD050
Dynamic load, C	184 kN
Rating life coefficient, A2	1.4
Static load, C0	232 kN
Fatigue limit load, Cu	28.3 kN
Nlim (oil)	4,800 rpm
Nlim (grease)	3,600 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz

Characteristic rolling element frequency, BSF	5.28 Hz
Characteristic outer ring frequency, BPF0	6.57 Hz
Characteristic inner ring frequency, BRFI	9.43 Hz
da max	62 mm
db min	62 mm
Da min	90 mm
Da max	100 mm
Db min	102 mm
Ca min	3 mm
Cb min	9 mm
ra max	2 mm
r1a max	2 mm