

Toyana TUP1 260.80 plain bearings

What is the 170 Outer Diameter (mm) best place to buy Toyana TUP1 260.80 plain bearings online? Manufacturing 110x170x28 Size (mm) 110 Bore Diameter (mm) Service .

Size (mm)	110x170x28
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Width (mm)	28
d	110 mm
D	170 mm
B	28 mm
C	28 mm
rn	0,5 mm
a	3,71 mm
b	3,5 mm
f	3,1 mm
r min.	2 mm
r0 max.	0,6 mm
D1	163,65 mm
D2	182,9 mm
da min.	119 mm
da max	124,5 mm
Da max.	161 mm
ra max.	2 mm
Weight	1,94 Kg
Basic dynamic load rating (C)	85 kN

Basic static load rating (C0)	73 kN
(Grease) Lubrication Speed	3 800 r/min
(Oil) Lubrication Speed	4 500 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.93
EAN	0029176034473
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	110MM Bore; 170MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6022NR
Weight / LBS	1.93
Outside Diameter	6.693 Inch 170 Millimeter
Outer Race Width	1.102 Inch 28 Millimeter

Bore	4.331 Inch 110 Millimeter
bore diameter:	110 mm
dynamic load capacity:	85000 N
outside diameter:	170 mm
static load capacity:	73000 N
overall width:	28 mm
precision rating:	ABEC 1 (ISO Class Normal)
bore type:	Round
finish/coating:	Uncoated
closure type:	Open
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	28 mm
snap ring included:	With Snap Ring
fillet radius:	2 mm
internal clearance:	C0
maximum rpm:	4500 RPM
operating temperature range:	Maximum of +250 °F
series:	60
SRI	9.86
hidYobi	6022NR
LangID	1
ro	0.6
D_	170
SREX	0.04
B_	28
da min	119
hidTable	ecat_NSRDGB
Oil rpm	4500

SRE	9.86
Cy	6.4
mass	1.94
GRS rpm	3800
ra	2
SRIX	0.04
D_a	161
SRIN	-0.04
C0	73
fo	15.5
SREN	-0.04
DE_	159.05
Prod_Type3	DGBB_SR_NR_OT
DA_	19.05
bomp	0
Z_	13
yobi	6022NR
Dx	185
C_conv	85000
ALPHA_	0
SDM_	140
r	2
KBRG	6101
SBRG	10
DI_	120.95