

Toyana TUP1 40.50 plain bearings

Online Toyana TUP1 40.50 plain bearings Expert. More Choices.
69 mm B Toyana TUP1 40.50 plain bearings 670 mm d in Stock &
820 mm D Ready to Ship Now!

d	670 mm
D	820 mm
B	69 mm
rs min	4 mm
Radial clearance class	CN
Mass	75.1 kg
Dynamic load, C	425 kN
Static load, C ₀	850 kN
Fatigue limit load, C _u	14.2 kN
N _{lim} (oil)	700 rpm
N _{lim} (grease)	500 rpm
Min operating temperature, T _{min}	-20 °C
Max operating temperature, T _{max}	120 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	16.7 Hz
Characteristic outer ring frequency, BPF ₀	12.7 Hz
Characteristic inner ring frequency, BPFI	14.31 Hz
da min	686 mm
Da max	804 mm

ra max	3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0692314560990
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	670MM Bore; 820MM Outside Diameter; 69MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove Riveted Solid Cage
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Outer Race Width	2.717 Inch 69 Millimeter
Bore	26.378 Inch 670 Millimeter
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter

32.283 Inch | 820
Millimeter