

Toyana TUP2 300.50 plain bearings

Online shopping 17 Outer Diameter (mm) Toyana TUP2 300.50 plain bearings from 30x17x7 Size (mm) a great selection at Store. ... Accessories.

Size (mm)	30x17x7
Bore Diameter (mm)	30
Outer Diameter (mm)	17
Width (mm)	7
d	17 mm
D	30 mm
B	7 mm
d1	20.4 mm
D2	27.7 mm
r1,2 – min.	0.3 mm
da – min.	19 mm
da – max.	20.3 mm
Da – max.	28 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	4.6 kN
Basic static load rating – C0	2.6 kN
Fatigue load limit – Pu	0.108 kN
Reference speed	50000 r/min
Limiting speed	26000 r/min
Calculation factor – kr	0.02
Calculation factor – f0	14.7
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.019
EAN	7316577662583
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	17MM Bore; 30MM Outside Diameter; 7MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 I
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61903 2Z
Weight / LBS	0.04
Bore	0.669 Inch 17 Millimeter
Outside Diameter	1.181 Inch 30 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
bore diameter:	17 mm
static load capacity:	2.55 kN
outside diameter:	30 mm

precision rating:	Not Rated
overall width:	7 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
outer ring width:	7 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
internal clearance:	C0
maximum rpm:	26000 RPM
dynamic load capacity:	4.62 kN
series:	61
d1 ≈	20.4 mm
D2 ≈	27.7 mm
r1,2 min.	0.3 mm
da min.	19 mm
da max.	20.3 mm
Da max.	28 mm
ra max.	0.3 mm
Basic dynamic load rating C	4.62 kN
Basic static load rating C0	2.55 kN
Fatigue load limit Pu	0.108 kN
Calculation factor kr	0.02
Calculation factor f0	14.7
Mass bearing	0.017 kg