

TR0608A KOYO Cu 12.6 32x75x29.75mm Tapered roller bearings

Bearing number	TR0608A
Size (mm)	32x75x29.75
Brand	KOYO
Bore Diameter (mm)	32
Outer Diameter (mm)	75
Width (mm)	29.75
d	32 mm
D	75 mm
T	29.75 mm
B	28 mm
C	23 mm
a	23.7 mm
r min.	1.5 mm
r2 min.	1.5 mm
da min.	40.5 mm
da max	41 mm
Da min	57 mm
Da max.	66.5 mm
Db min.	71 mm
ra max.	1.5 mm
rb max.	1.5 mm
Weight	0.649 Kg
Basic dynamic load rating (C)	75.1 kN
Basic static load rating (C0)	87.1 kN

(Grease) Lubrication Speed	5600 r/min
(Oil) Lubrication Speed	7400 r/min
Calculation factor (e)	0.55
Calculation factor (Y0)	0.6
Bearing No.	TR0608A
r(min)	1.5
r1(min)	1.5
Cr	93.8
C0r	87.1
Cu	12.6
Grease lub.	5600
Oil lub.	7400
a(mm)	23.7
da(min)	40.5
db(max)	41
Da(max)	66.5
Da(min)	57
Db(min)	71
Sa(min)	3
Sb(min)	6.5
ra(max)	1.5
rb(max)	1.5
e	0.55
Y1	1.10
Y0	0.60
(Refer.) Mass (kg)	0.649