

UKT213H+WB SNR Adapter sleeve reference H2313 Bearing units

| | |
|--------------------------|------------|
| A1 | 26 mm |
| A5 | 32 mm |
| B1 | 65 mm |
| d1 | 85 mm |
| G | M6x1 |
| H1 | 151 mm |
| H2 | 111 mm |
| L1 | 137 mm |
| L3 | 121 mm |
| N1 | 32 mm |
| N2 | 70 mm |
| C | 57.2 kN |
| C0 | 40 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Adapter sleeve reference | H2313 |
| Designation of housing | T213- |
| Designation of bearing | UK213G2H |
| Bearing number | UKT213H+WB |
| Brand | SNR |
| Bore Diameter (mm) | 60 |
| d | 60 mm |
| A4 | 699 mm |
| P | 300 mm |
| e | 38 mm |

| | |
|-------------------------------|---------|
| L2 | 144 mm |
| s1 | 32 mm |
| SW | 24 mm |
| A | 65 mm |
| B | 65 mm |
| D2 | 85 mm |
| H | 322 mm |
| J | 260 mm |
| L | 606 mm |
| M | 260 mm |
| M1 | 22 mm |
| N | 15 mm |
| T | 6 mm |
| A2 | 70 mm |
| Weight | 25.3 Kg |
| Basic dynamic load rating (C) | 57.2 kN |