

UKT308H SNR H 124 mm Bearing units

| | |
|--------------------------|----------|
| A2 | 34 mm |
| A5 | 27.5 mm |
| B1 | 46 mm |
| d1 | 58 mm |
| G | M6x1 |
| H2 | 83 mm |
| N2 | 50 mm |
| C | 40.56 kN |
| C0 | 24 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Adapter sleeve reference | H2308 |
| Designation of housing | T308- |
| Designation of bearing | UK308G2H |
| Bearing number | UKT308H |
| Brand | SNR |
| Bore Diameter (mm) | 35 |
| d | 35 mm |
| L4 | 89 mm |
| L5 | 22 mm |
| L2 | 19 mm |
| L3 | 100 mm |
| s1 | 27.5 mm |
| A | 50 mm |
| A1 | 34 mm |

| | |
|-------------------------------|----------|
| B | 46 mm |
| D2 | 58 mm |
| H | 124 mm |
| H1 | 83 mm |
| L | 162 mm |
| L1 | 55.5 mm |
| N | 32 mm |
| N1 | 50 mm |
| Thread (G) | M6x1 |
| J1 | 18 mm |
| J2 | 112 mm |
| Weight | 3 Kg |
| Basic dynamic load rating (C) | 40.56 kN |