

UKT319H SNR Basic dynamic load rating (C) 156 kN Bearing units

| | |
|--------------------------|----------|
| A2 | 72 mm |
| A5 | 52 mm |
| B1 | 90 mm |
| d1 | 125 mm |
| G | M10x1 |
| H2 | 165 mm |
| N2 | 106 mm |
| C | 156 kN |
| C0 | 122 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Adapter sleeve reference | H2319 |
| Designation of housing | T319- |
| Designation of bearing | UK319G2H |
| Bearing number | UKT319H |
| Brand | SNR |
| Bore Diameter (mm) | 85 |
| d | 85 mm |
| L4 | 180 mm |
| L5 | 46 mm |
| L2 | 33 mm |
| L3 | 197 mm |
| s1 | 52 mm |
| A | 110 mm |

| | |
|-------------------------------|---------|
| A1 | 72 mm |
| B | 90 mm |
| D2 | 125 mm |
| H | 270 mm |
| H1 | 165 mm |
| L | 322 mm |
| L1 | 107 mm |
| N | 57 mm |
| N1 | 106 mm |
| Thread (G) | M10x1 |
| J1 | 35 mm |
| J2 | 240 mm |
| Weight | 26.2 Kg |
| Basic dynamic load rating (C) | 156 kN |