

# USSP207 SNR Thread (G) R1/8"

## Bearing units

|   |               |
|---|---------------|
| B   | 32 mm         |
| A5  | 23.5 mm       |
| G   | R1/8"         |
| H2  | 41 mm         |
| s1  | 16 mm         |
| S   | 8.5 mm        |
| SW  | 3 mm          |
| C   | 25.7 kN       |
| C0  | 15.2 kN       |
| T min.                                      | -20 °C        |
| T max.                                      | 100 °C        |
| Recommended tightening torque for set screw | 5.5 Nm        |
| Designation of housing                      | SP206-207/72- |
| Designation of bearing                      | US207G2       |
| Bearing number                              | USSP207       |
| Brand                                       | SNR           |
| Bore Diameter (mm)                          | 35            |
| d   | 35 mm         |
| s   | 8.5 mm        |
| A   | 21 mm         |
| B1  | 32 mm         |
| D1  | 48 mm         |
| H   | 98 mm         |
| H1  | 41 mm         |
| L   | 274 mm        |

|                               |         |
|-------------------------------|---------|
| L1                            | 225 mm  |
| Thread (G)                    | R1/8"   |
| Weight                        | 2 Kg    |
| Basic dynamic load rating (C) | 25.7 kN |