

# Worm Gear Slew Drive for Mist Cannon Truck Se9

Online 0.0 Inventory Worm Gear Slew Drive for Mist Cannon Truck Se9 Expert.More Choices. Worm Gear Slew Drive for Mist Cannon Truck Se9 in Stock & Ready to Ship Now!

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 24.97  |
| EAN                       | 0883450383240  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 6  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 6 Bolt Round Flange Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22222  |
| Seals                     | Double Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | No Pilot   |
| Inch – Metric             | Metric   |
| Long Description          | 6 Bolt Round Flange Block; 110MM Bore; 327.7MM Bolt Circle; 163.576MM Bolt Spacing; 1 Piece Solid; E |

|                                       |                                |
|---------------------------------------|--------------------------------|
| Other Features                        | Double Row                     |
| UNSPSC                                | 31171501                       |
| Harmonized Tariff Code                | 8483.20.40.80                  |
| Noun                                  | Bearing                        |
| Keyword String                        | Flanged                        |
| Weight / LBS                          | 55                             |
| D                                     | 5.53 Inch   140.462 Millimeter |
| Nominal Bolt Circle Diameter<br>Round | 12.9 Inch   327.7 Millimeter   |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter          |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter          |
| d                                     | 4.331 Inch   110 Millimeter    |
| Bolt Spacing                          | 6.44 Inch   163.576 Millimeter |