

ZEN 61818-2RS deep groove ball bearings

Request A Quote For Your 80,000 Outer Diameter (mm) Special ZEN 61818-2RS deep groove ball bearings Needs Today! Free Quotes. ISO 40x80x30.162 Size (mm) 9001 certified.

Size (mm)	40x80x30.162
Bore Diameter (mm)	40,000
Outer Diameter (mm)	80,000
Width (mm)	30,162
d	40,000 mm
D	80,000 mm
B	30,162 mm
C	30,162 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359581423
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal

Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 30.18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
Other Features	Deep Groove Cartridge Type Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.28
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Bore	1.575 Inch 40 Millimeter
Outer Race Width	1.188 Inch 30.18 Millimeter
bore diameter:	40 mm
static load capacity:	2390 N
outside diameter:	80 mm
precision rating:	ISO Class 0
overall width:	30.2 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot

inner ring width:	30.20 mm
snap ring included:	Without Snap Ring
outer ring width:	30.20 mm
internal clearance:	CN
maximum rpm (grease):	8700 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1.1 mm
dynamic load capacity:	5100 N
manufacturer product page:	Click here