

# ZEN P6308-SB deep groove ball bearings

What is the best 0.0 Inventory place to buy ZEN P6308-SB deep groove ball bearings online? Manufacturing Service .

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	65.83
EAN	7316576668654
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Shaft Mount
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Insert Part Number	22322 CC/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Metric
Other Features	Double Row   Heavy Duty
Long Description	2 Bolt Pillow Block; 110MM Bore; 152.4MM Base to Center Height; Shaft Mount Mount; Spherical Roller

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 22322
Weight / LBS	145
Bolt Spacing Maximum	16 Inch   406.4Millimeter
D	8.125 Inch   206.375 Millimeter
d	4.331 Inch   110 Millimeter
Bolt Spacing Minimum	14.625 Inch   371.475Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
B	6 Inch   152.4 Millimeter
Nominal Bolt Center to Center	15.3 Inch   389 Millimeter
da	110 mm
db	123.825 mm
dc	106.375 mm
Da	240 mm
Ca	89.789 mm
A1	133.35 mm
A2	206.375 mm
S	4.763 mm
ba	63.5 mm
H	287.337 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm

L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	61.119 mm
Housing	SAF 322
Bearing	22322 E
Lock nut	AN 22
Lock washer	W 22
Stabilizing ring	SR-0-22
Labyrinth ring (db shaft position)	LOR 121
Labyrinth ring (dc shaft position)	LOR 113
End plug (suffix Y)	EPR 14
Bearing limiting speed	2800 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	54.7 kN
Mass pillow block	65.8 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC

Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g