

# ZEN S1623-2Z deep groove ball bearings

How do I place an EMERGENCY order for a ZEN S1623-2Z deep groove ball bearings that I want to pick up at a 241.3 mm da our store?

da	241.3 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	304.8 mm
ba	96.838 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	69.85 mm
Housing	SAF 052 KA
Bearing	23052 CCK/W33
Adapter sleeve assembly	SNP 3052×9.1/2

Stabilizing ring	2 x A8898
Labyrinth ring	2 x LOR 178
PosiTrac Plus contact element	2 x B10724-178
End plug (suffix Y)	X-5217-2
Max. speed for PosiTrac Plus seal	600 r/min
P60°	423 kN
P90°	254 kN
P120°	160 kN
P150°	145 kN
P180°	173 kN
Pa	81.4 kN
Mass pillow block	247 kg
Cap bolt	4 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g