

# ZEN S2201 self aligning ball bearings

ZEN S2201 self aligning ball bearings Deal is your source for 17 mm d OEM and accessories. We 10 mm B sell 35 mm D Genuine at discount prices.

d	17 mm
D	35 mm
B	10 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.04 kg
Dynamic load, C	6.8 kN
Static load, C <sub>0</sub>	3.35 kN
Fatigue limit load, C <sub>u</sub>	0.15 kN
f <sub>0</sub>	13.6
N <sub>lim</sub> (grease)	14,000 rpm
Min operating temperature, T <sub>min</sub>	-25 °C
Max operating temperature, T <sub>max</sub>	110 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.47 Hz
Characteristic outer ring frequency, BPF <sub>0</sub>	3.14 Hz
Characteristic inner ring frequency, BPFI	4.86 Hz
da min	19 mm
da max	21 mm

Da max	33 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.039
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	17MM Bore; 35MM Outside Diameter; 10MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1   ISO P0; No F
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.08598

Bore	0.669 Inch   17 Millimeter
Outer Race Width	0.394 Inch   10 Millimeter
Outside Diameter	1.378 Inch   35 Millimeter
Inner Race Width	0 Inch   0 Millimeter