

ZEN S61928-2RS deep groove ball bearings

What is the best 65 Outer Diameter (mm) place to buy ZEN S61928-2RS deep groove ball bearings online? Manufacturing Service . 120x65x23 Size (mm)

Size (mm)	120x65x23
Bore Diameter (mm)	120
Outer Diameter (mm)	65
Width (mm)	23
d	65 mm
D	120 mm
B	23 mm
d1	83.3 mm
D2	105.8 mm
D3	115.21 mm
D4	129.7 mm
b	3.1 mm
C	4.06 mm
f	2.82 mm
r0	0.6 mm
r1,2 – min.	1.5 mm
da – min.	74 mm
da – max.	83.2 mm
Da – max.	111 mm
Db – min.	131 mm
ba – min.	3.5 mm
Ca – max.	6.88 mm

ra – max.	1.5 mm
Basic dynamic load rating – C	60.5 kN
Basic static load rating – C0	58.5 kN
Fatigue load limit – Pu	2.5 kN
Reference speed	10000 r/min
Limiting speed	4800 r/min
Calculation factor minimum radial load – kr	0.04
Mass bearing	1.05 kg
d1 ≈	83.3 mm
D2 ≈	105.8 mm
r0 max.	0.6 mm
r1,2 min.	1.5 mm
da min.	74 mm
da max.	83.2 mm
Da max.	111 mm
Db min.	131 mm
ba min.	3.5 mm
Ca max.	6.88 mm
ra max.	1.5 mm
Basic dynamic load rating C	60.5 kN
Basic static load rating C0	58.5 kN
Fatigue load limit Pu	2.5 kN
Calculation factor kr	0.04
Snap ring	SP 120