

ZEN S686-2TS4,5 deep groove ball bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products at Low 60 mm d Costs. 31 mm B

| | |
|---|-----------|
| d | 60 mm |
| D | 130 mm |
| B | 31 mm |
| rs min | 2.1 mm |
| Radial clearance class | C4 |
| Mass | 1.73 kg |
| Dynamic load, C | 82 kN |
| Static load, C0 | 52 kN |
| Fatigue limit load, Cu | 2.36 kN |
| f0 | 13.2 |
| Nlim (grease) | 5,400 rpm |
| Min operating temperature, Tmin | -25 °C |
| Max operating temperature, Tmax | 110 °C |
| Characteristic cage frequency, FTF | 0.38 Hz |
| Characteristic rolling element frequency, BSF | 4.09 Hz |
| Characteristic outer ring frequency, BPF0 | 3.07 Hz |
| Characteristic inner ring frequency, BPFI | 4.93 Hz |
| da min | 71 mm |
| da max | 80.5 mm |
| Da max | 119 mm |

| | |
|---------------------------------|--|
| ra max | 2 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.717 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Non-Contact Seal |
| Internal Clearance | C4-Extra Loose |
| Inch – Metric | Metric |
| Long Description | 60MM Bore; 130MM Outside Diameter; 31MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove Non-Friction Nitrile Rubber Seal |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Weight / LBS | 3.70376 |
| Outer Race Width | 1.22 Inch 31 Millimeter |
| Bore | 2.362 Inch 60 Millimeter |

| | |
|------------------|-----------------------------|
| Outside Diameter | 5.118 Inch 130 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |