

ZEN S686-2TS4,5 deep groove ball bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products at Low 60 mm d Costs. 31 mm B

d	60 mm
D	130 mm
B	31 mm
rs min	2.1 mm
Radial clearance class	C4
Mass	1.73 kg
Dynamic load, C	82 kN
Static load, C0	52 kN
Fatigue limit load, Cu	2.36 kN
f0	13.2
Nlim (grease)	5,400 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.09 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BRFI	4.93 Hz
da min	71 mm
da max	80.5 mm
Da max	119 mm

ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.717
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	60MM Bore; 130MM Outside Diameter; 31MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	3.70376
Outer Race Width	1.22 Inch 31 Millimeter
Bore	2.362 Inch 60 Millimeter

Outside Diameter	5.118 Inch 130 Millimeter
Inner Race Width	0 Inch 0 Millimeter