

# ZEN WR4-2Z deep groove ball bearings

How do I place an EMERGENCY order for a ZEN WR4-2Z deep groove ball bearings that I want to pick up 90 mm da at a our store?  
104.775 mm db

da	90 mm
db	104.775 mm
dc	85.725 mm
Da	160 mm
Ca	48.809 mm
A1	98.425 mm
A2	206.375 mm
S	4.763 mm
ba	40.481 mm
H	196.85 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J1	53.975 mm
L	349.25 mm
N1	19.05 mm
R1	60.325 mm
R2	27.781 mm
RG	3/8 NPT
PG	1/8 NPT
h	38.1 mm

Housing	FSAFS 218
Bearing	22218 E
Lock nut	AN 18
Lock washer	W 18
Stabilizing ring	SR-18-15
Taconite seal (db shaft position)	TER 112
Taconite seal (dc shaft position)	TER 191
End plug (suffix Y)	EPR 11
Max. speed for Taconite seal	750 r/min
P60°	157 kN
P90°	94.3 kN
P120°	59.6 kN
P150°	54.3 kN
P180°	64.9 kN
Pa	41.8 kN
Mass pillow block	29 kg
Cap bolt	1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	141.75 g