

ZVL 32005AX tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all your ZVL 32005AX tapered roller bearings needs – including routine maintenance, major repairs, warranty Quote Days to Ship service, 140 I.D.(Ø) and equipment inspections.

Days to Ship	Quote
RoHS	6
I.D.(Ø)	140
O.D.(Ø)	300
Width(mm)	62
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Outer Ring Type	Flat
Retainer Type	Momi removing
Rotational Speed(rpm)	2000
Basic Load Rating, Dynamic Rating(N)	665000
Basic Load Rating, Static Rating(N)	795000
Clearance sign	C3
Accuracy(Class)	Class 0
Bearing Ring Type	Type NJ
Acoustic Symbol	No
Holder Symbol	M
Symbol of Bearing Ring Shape	E
Seal, Shield Symbols	No
Precision Grade Symbol	No

Symbol of contact angle	No
Special Configurations Code	No
Symbols of Lubrication Amount	No
Internal Symbol	No
Raceway Ring Shape	Cylindrical Roller
Load Direction	Radial
Inner/Outer Ring Material	Steel
Outer Ring	With Outer Ring
Precision (JIS)	Grade 0
Specifications	Standard
Rolling Element Material	Steel
Holder Color	No
Low Torque Specification	No
Material Symbol	No