

# ZVL K-L44643/K-L44610/K-L44600LA tapered roller bearings

What are the dimensions of a ZVL K-L44643/K-L44610/K-L44600LA tapered roller bearings? 17x26x5 Size (mm) 26 Outer Diameter (mm) Manufacturing Service . Get Your 17 Bore Diameter (mm) Free, Instant Quote

Size (mm)	17x26x5
Bore Diameter (mm)	17
Outer Diameter (mm)	26
Width (mm)	5
d	17 mm
D	26 mm
B	5 mm
C	5 mm
r min.	0,3 mm
da min.	19 mm
da max	19,5 mm
Da max.	24 mm
ra max.	0,3 mm
Weight	0,008 Kg
Basic dynamic load rating (C)	2,23 kN
Basic static load rating (C0)	1,46 kN
(Grease) Lubrication Speed	24 000 r/min
(Oil) Lubrication Speed	28 000 r/min
rs min	0.3 mm
Radial clearance class	CN

Mass	0.008 kg
Dynamic load, C	2.23 kN
Static load, C0	1.46 kN
Fatigue limit load, Cu	0.07 kN
f0	16.1
Nlim (oil)	28,000 rpm
Nlim (grease)	24,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.92 Hz
Characteristic outer ring frequency, BPF0	7.11 Hz
Characteristic inner ring frequency, BRFI	8.89 Hz
da min	19 mm
Da max	24 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.014
EAN	4547359006117
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No

Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	17MM Bore; 26MM Outside Diameter; 5MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fill
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.018
Inner Race Width	0 Inch   0 Millimeter
Bore	0.669 Inch   17 Millimeter
Outside Diameter	1.024 Inch   26 Millimeter
Outer Race Width	0.197 Inch   5 Millimeter